



**CPT - 872**  
Wireless Gas Detector



**CPT - 873**  
Wireless Magnetic Transmitter/  
Vibration Detector



**CPT - 871**  
Wireless Smoke Detector



**CPT - 868**  
Control Unit




**CPT - 869**  
Passive I/R Detector/Transmitter

AUTHORISED DEALER



**CPT - 870**  
Remote Control



MODAL NO	CPT - 868	CPT - 869	CPT - 870	CPT - 871	CPT - 872	CPT - 873
VOLTAGE	AC12V Adaptor	9V alkaline battery	12V alkaline battery	9V alkaline battery	230AC	12V alkaline battery
STANDBY CURRENT	100mA	15µA	0µA	under 2.5µA	1W	0µA
FREQUENCY	Oscillated by SAW Resonator 320	Oscillated by SAW Resonator 320	Oscillated by SAW Resonator 320	Oscillated by SAW Resonator 320	Oscillated by SAW Resonator 320	Oscillated by SAW Resonator 320
TEMPERATURE	-	0°C - 40°C	-	0°C - 50°C	-10°C to 50°C	-
BROADCAST RANGE	No Obstruction 100 feet	No Obstruction 30 feet	No Obstruction 100 feet	-	-	No Obstruction 100 feet
DIMENSION (MM)	230 x 175 x 60	110 x 68 x 46	65 x 40 x 11	∅84 x 77+93 x 66 x 24	140 x 85 x 40+93 x 66 x 240	62 x 38 x 16
WEIGHT (GM)	1150gm	120gm	40gm	280gm	500gm	40gm